

Super Leichtlauf 10W-40

Description

Low-friction motor oil based on synthetic technology. For the high demands of modern, high-performance gasoline and diesel engines without extended maintenance intervals. Provides optimal wear protection and helps preserve the integrity of sealing materials, thereby maintaining engine sealing performance. This makes it particularly suitable for year-round use in vehicles with more than 100,000 km (62,000 miles) of mileage.

Properties

- outstanding engine cleanliness
- tested for turbochargers and catalytic converters
- smooth engine running
- miscible with all commercially available motor oils
- optimum stability to aging
- high shear stability
- instant lubrication after cold start
- high lubrication reliability
- excellent wear protection
- regenerates seals
- especially suitable for vehicles with mileages over 100,000 km
- maintains seals

Specifications / Approvals

ACEA A3 • ACEA B4 • API SP • MB-Approval 229.3 • VW 501 01 • VW 505 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Fiat 9.55535-D2 • Fiat 9.55535-G2 • GWM • Haval • MB 229.1 • Peugeot Citroen (PSA) B71 2300 • Renault RN 0700 • Renault RN 0710 • Wuling

Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,870 g/cm ³ DIN 51757
Viscosity at 40 °C	97,0 mm ² /s ASTM D7042
Viscosity at 100 °C	14,5 mm ² /s ASTM D7042
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	≤ 7000 mPas ASTM D5293
Viscosity index	155 DIN ISO 2909



Technical data

HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	11,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	11,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	2,5 DIN ISO 2049

Areas of application

Ideal for vehicles with mileages of over 100,000 km and for modern gasoline, diesel and turbocharged engines.

Available pack sizes

1 l Canister plastic	9503 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
1 l Canister plastic	21236 AR-DZAR-EN-FR
4 l Canister plastic	9504 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	9505 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	20671 DZAR-EN-FR
20 l Canister plastic	1304 DE-EN-ES-IT-PT
60 l Black plate barrel	1302 DE-EN-ES-FR-IT-PT

Product information

PI 61/10/21/2026



Super Leichtlauf 10W-40

Available pack sizes

205 l Black plate 1303
barrel DE-EN-ES-FR-IT-PT

**Our information is based on thorough research
and may be considered reliable, although not
legally binding.**